

NX Four Spiral Hose

Exceeds the requirements of SAE 100R12 - EN856



- Tube: Nitrile
- Reinforcement: Four spirals of high tensile wire
- Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: 40°C to +121°C (-40°F to +250°F)
- Packaging: Coils
- Application: Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BURST PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE Non-Skive COUPLINGS	ONE PIECE Skive COUPLINGS
	(in)	(in)	(mm)	(in)			(mm)				
NX-06	3/8	0.79	20	5,000	20,000	5.0	127	0.40	N, V		
NX-08	1/2	0.94	24	5,000	20,000	7.0	178	0.54	N, V		
NX-10	5/8	1.06	27	5,000	20,000	8.0	203	0.74	N		
NX-12	3/4	1.26	32	5,000	20,000	9.5	241	0.89	N, V		
NX-16	1	1.50	38	5,500	22,000	12.0	305	1.30	N, V		
NX-20	1 1/4	1.81	46	5,000	20,000	16.5	419	1.79	N	VS	
NX-24	1 1/2	2.13	54	4,300	17,200	20.0	508	2.06	N	VS	
NX-32	2	2.68	68	3,600	14,400	25.0	635	2.78	N	VS	

QC-HB Four Spiral Hose (Half Bend)

Meets or exceeds the requirements of SAE 100R12 - EN856
(Half the bend radius of SAE100R12)



- Tube: Seamless, black, oil and heat resistant synthetic rubber
- Reinforcement: Four spirals of high tensile wire
- Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: -40°C to +121°C (-40°F to +250°F)
- Packaging: Coils
- Application: Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BURST PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE Non-Skive COUPLINGS	ONE PIECE Skive COUPLINGS
	(in)	(in)	(mm)	(in)			(mm)				
QC-06HB	3/8	0.80	20	4,000	16,000	2.5	64	.40	N, V		
QC-08HB	1/2	0.94	24	4,000	16,000	3.5	89	.54	N, V		
QC-10HB	5/8	1.08	27	4,000	16,000	4.0	102	.74	N		
QC-12HB	3/4	1.21	31	4,000	16,000	4.8	121	.94	N, V		
QC-16HB	1	1.50	38	4,000	16,000	6.0	153	1.34	N, V		
QC-20HB	1 1/4	1.85	47	3,000	12,000	8.3	210	1.74	N	VS	
QC-24HB	1 1/2	2.10	53	2,500	10,000	10.0	254	2.01	N	VS	
QC-32HB	2	2.63	67	2,500	10,000	12.5	318	2.75	N	VS	

* Hose can also be used with OEM reuseable couplings.