

Hose

LX 100R3 Rubber Cover Fabric Braid

Meets or exceeds the requirements of SAE 100R3

- Tube: Black, oil and heat-resistant synthetic rubber
- Reinforcement: Two braid of synthetic yarn
- Cover: Black, oil abrasion and weather resistant synthetic rubber
- Temperature: -40°C to +100°C (-40°F to +212°F)
- Packaging: Reels
- Application: Petroleum based hydraulic fluids and pneumatic service



PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BURST PRESSURE (psi)		MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS
	(in)	(mm)	(in)	(mm)		(in)	(mm)	(in)	(mm)		
LX-04	¼	0.56	14.3	1,250	5,000	3.0	76	0.12	E		
LX-06	¾	0.75	19.0	1,125	4,500	4.0	102	0.17	E, N		
LX-08	½	0.94	23.8	1,000	4,000	5.0	127	0.25	E, N		

PROJET® 4000 4000 PSI Pressure Wash

- Tube: Seamless, black synthetic rubber
- Reinforcement: One braid of high tensile steel wire
- Cover: Wrapped abrasion & weather resistant synthetic rubber, Black, Blue or Gray
- Temperature: -29°C to +121°C (-20°F to +250°F)
- Packaging: 50' 100' 150' 200' Bulk Reels
- Application: Pressure wash equipment and agricultural wash down spraying



PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS	COVER
	(in)	(mm)	(in)	(mm)		(in)	(mm)			
PJ4-06BK	¾	0.61	15.5	4,000	3.5	90	0.16	E	Wrapped	
PJ4-06BL	¾	0.61	15.5	4,000	3.5	90	0.16	E	Wrapped	
PJ4-06GY	¾	0.61	15.5	4,000	3.5	90	0.16	E	Wrapped	

PROJET® 4000 4000 PSI Pressure Wash

- Tube: Seamless, black synthetic rubber
- Reinforcement: One braid of high tensile steel wire
- Cover: Smooth abrasion & weather resistant synthetic rubber, Blue
- Temperature: -29°C to +121°C (-20°F to +250°F)
- Packaging: 50' 100' 150' 200' Bulk Reels
- Application: Pressure wash equipment and agricultural wash down spraying



PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE COUPLINGS	COVER
	(in)	(mm)	(in)	(mm)		(in)	(mm)			
PJ4-04BLM	¼	0.48	12.2	4,000	2.9	75	.19	E	Smooth	
PJ4-06BLM	¾	0.61	15.5	4,000	3.5	90	.24	E	Smooth	