

Gamma-HEAT

HOT AIR BLOWER HOSE



General Properties and Applications


Gamma-HEAT's premium-grade materials make for reliable service life connecting the blower to flow lines on dry-bulk trailers. Withstands intermittent temperatures up to 350°. Spring steel helix wire resists kinking.



Technical Data

Construction	Type "E"
Tube	Black, High heat resisting EPDM
Cover	Black or Brown, EPDM
Temperature	-50°F to +225°F continuous, 350°F intermittent
Safety Factor	4:1
Reinforcement	High tensile strength tire cord plies, Steel helix wire
Branding	HOT AIR BLOWER HOSE 150 PSI WP (Yellow layline with black letters)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Bend Radius (in.)	Working Pressure (psi)	Weight / Foot (lbs.)
3"	GHE15S1-3.0	3-33/64"	100'/200'	12"	150	1.75
4"	GHE15S1-4.0	4-9/16"	100'/200'	16"	150	2.40



Cut Lengths Available



Tex-TIP:

Check out the useful features on Texcel's web site www.texcelrubber.com today including Fractional Measurement Equivalents.



Call or Email Maumee Hose & Belting for Pricing

Ph. 419-893-7272 • Fax 419-893-4744 • Email: info@maumeehose.com • Web: www.maumeehose.com
720 Illinois Avenue • Maumee, Ohio 43537 USA