

Tex-MP 300

MULTI-PURPOSE HOSE 300 PSI



General Properties and Applications

Excellent quality multi-purpose hose for applications calling for oil resistance and higher working pressures. Tube handles oil-laden air, lubricating oils and mild alkalis or caustic solutions.

Technical Data

Construction	Type "A"
Tube	Black, Nitrile (RMA Class B Medium Oil Resistance)
Cover	Red, Nitrile/PVC
Temperature	-20°F to +180°F
Reinforcement	One or two spiral polyester cords
Branding	TEXCEL MP300 MULTI-PURPOSE SIZE – WP – LOT CODE (White letters)
Packaging	Reels

Inside Diameter (in.)	Package Type	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Foot (lbs.)
1/4"	Reel	MP-4-R300-600R	9/16"	600'	300	0.13
3/8"	Reel	MP-6-R300-600R	23/32"	600'	300	0.22
1/2"	Reel	MP-8-R300-600R	7/8"	600'	300	0.31
3/4"	Reel	MP-12-R300-600R	1-7/32"	600'	300	0.48
1"	Reel	MP-16-R250-400R	1-7/16"	400'	250	0.66
1-1/4"	Reel	MP-20-20-300	1-3/4"	300'	200	0.69
1-1/2"	Reel	MP-24-15-250	2"	250'	200	0.80

✓ Sold in Standard Lengths Only



Tex-TIP:

Tex-MP 300 has an oil-resistant tube to extend service life in applications with oil mixtures.



Call or Email Maumee Hose & Belting for Pricing

Ph. 419-893-7272 • Fax 419-893-4744 • Email: info@maumeehose.com • Web: www.maumeehose.com
720 Illinois Avenue • Maumee, Ohio 43537 USA