



# Tex-PUSH-ON 300

## GENERAL SERVICE AIR WATER HOSE

### General Properties and Applications

A braided hose that allows for the quick and easy insertion of push-on fittings with no special crimping tools required. The superb coupling retention is achieved by the gripping pressure of the internal polyester design. With proper installation, fittings will not give under normal working pressure. The tube and cover offer high oil resistance, 300psi working pressures, and non-conductive properties and are an effective option for industrial and other applications where a durable, convenient hose is a must.

NOTE: Not recommended for unleaded gasoline.

### Technical Data

Tube	NBR (RMA Class A)
Cover	NBR/PVC (RMA Class A)
Reinforcement	One braid polyester cords
Safety Factor	4:1
Temperature	-20°F to +180°F
Branding	<b>TEXCEL</b> Push-on 300 <ID> 300 PSI WP - LOT (White ink letters)

Inside Diameter (in.)	Package Type	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Package (lbs.)
1/4"	Reel	PUSH-4-250	32/64"	250'	300	27.50
3/8"	Reel	PUSH-6-250	42/64"	250'	300	36.75
1/2"	Reel	PUSH-8-250	52/64"	250'	300	51.75
5/8"	Reel	PUSH-10-250	60/64"	250'	300	61.50
3/4"	Reel	PUSH-12-250	1-6/64"	250'	300	80.25

✓ Sold in Standard Lengths Only

