

# Sigma-URE-HD-BLUE

## HD Polyurethane Material Handling Hose



### General Properties and Applications

Premium quality material handling hose designed with a thick, heavy-duty, smooth Polyurethane lining. Ideal for dry applications where high abrasion resistance is required.

### Technical Data

Construction	Type "G"
Tube	Clear, thick, heavy-duty smooth Polyurethane Lining
Cover	Blue, HMW PVC formulated for static dissipation, provides flexibility in sub-zero temperatures.
Temperature	-40°F to +160°F
Safety Factor	3:1
Reinforcement	Rigid PVC helix
Branding	Sigma Series PVC-URE-HD-BLUE – <ID> - LOT
Compare to	Ureflex-2



Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Liner Thickness (mm)	Standard Length (ft.)	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius (in.)	Weight / Foot (lbs.)
2"	SPVC-URE-HB-2.0	2.43"	1.2	100'	40	30	4"	0.59
3"	SPVC-URE-HB-3.0	3.70"	1.8	100'	40	30	6"	1.23
4"	SPVC-URE-HB-4.0	4.80"	2.0	100'	35	30	10"	2.02
5"	SPVC-URE-HB-5.0	5.80"	2.0	20, 50, 100'	35	28	15"	2.57
6"	SPVC-URE-HB-6.0	6.87"	2.3	20, 50, 100'	30	28	18"	3.84

- ✓ Sold in Standard Lengths Only
- ✓ Above specifications at 70°F operating temperature



**Call or Email Maumee Hose & Belting for Pricing**

Ph. 419-893-7272 • Fax 419-893-4744 • Email: [info@maumeehose.com](mailto:info@maumeehose.com) • Web: [www.maumeehose.com](http://www.maumeehose.com)  
720 Illinois Avenue • Maumee, Ohio 43537 USA